



PocketPOS™ P200 technical specifications

Available in "3G", "GPRS" and "Wifi" versions

Processor	32 bit Highly Secure CPU
Memory	16MB SDRAM, 16MB Nor-Flash
Display	128x64, Built-in Icons, Backlight
Sound	Multi-tone Beeper
Keypad	18 Keys, Clear Plastic
LED's	Four LED's (Green, Yellow, Blue and Red)
Communication Ports	USB (USB 2.0, Slave, Mini-USB B) Serial (RS232) Bluetooth (Class 2 - 10 meter, V2.1+EDR)
Available Communication Module	850/900/1800/1900 GPRS Module
Battery/Power	1800mAh, 7.4V, Lithium-Polymer battery 1000mAh, 7.4V, Lithium-Polymer battery (available in Printerless Version) AC charging adapter 100-240VAC, 50/60 Hz
Printer	48mm, 203dpi, thermal printer (optional)
Paper Size	58mm / 2.3 in (width), 30mm / 1.2 in (roll diameter)
Card Reader	MSR (ISO-7811, 1/2/3 track, Bi-directional) IC card Reader (ISO-7816, EMV/T=0 & T=1) SAM Module (ISO-7816, 5V)
Certifications	EMV Level1 Level2 PCI PTS 3.0 FCC、 CE
RTC	Built-in
Key Management	DUKPT
Apple MFi support	iPad, iPhone, iPod Touch (iOS 4.0 or higher)
Dimensions(W x D x H)	79×146×37mm / 3.1×5.7×1.5" 79×146×42mm / 3.1×5.7×1.7" (3G/GPRS/Wifi)
Weight	400g / 14.1oz / 0.88 lbs (paper and battery included) (Bluetooth) 408g / 14.4oz / 0.90 lbs (paper and battery included) (3G/GPRS/Wifi)
Environment	Operating temperature: 0 ~ 40°C (+32 ~ 104°F) Operating humidity: 20 ~ 85% RH Storage temperature: -20 ~ 60°C (-4 ~ 140°F) Storage humidity: 10~ 90% RH

All features and specifications are subject to change without notice. All trademarks mentioned are registered by their respective owners. Contact Blue Bamboo sales for more details.

Blue Bamboo Corporate Offices
5 Floor, Huishan Technology Park,
3333 Changning Road, Shanghai China 200336
Tel: +86 21 5219 0333 Fax: +86 21 5219 0603
USA Office Tel: 1-888-372-9266



BLUE BAMBOO®