






# PocketPOS™ P25i technical specifications

<b>Communication Interface</b>	Bluetooth® Class 2, up to 32 feet (10 meter) Version 2.0 + EDR SPP (Serial Port Profile) required by host device, USB 2.0. *optional: Version 2.1 + EDR SPP (Serial Port Profile)
<b>Indicator</b>	Tricolor LED for Power, Bluetooth®, Error Message
<b>Keypad</b>	Power, Feed and Mode buttons
<b>Print Method</b>	Direct thermal
<b>Print Width</b>	48mm (1.89" )
<b>Feed Speed</b>	50 mm/sec (2.0" /sec)
<b>Print Speed</b>	50 mm/sec (2.0" /sec)
<b>Paper Size</b>	58 mm (2.3" ) width, 40 mm (1.6" ) roll diameter, 11mm (0.43" ) inner diameter
<b>Print Resolution</b>	203 dpi horizontal & vertical
<b>Graphic Mode</b>	384 dots wide (max.), length unlimited
<b>Character Sets</b>	Latin alphabet: 12 x 24, 16 x 32 (Lucide font) Chinese characters: 24 x 24, 32 x 32 Scalable up to 8 times original size
<b>Bar Code</b>	UPC-A, UPC-E, EAN-8, EAN-13, PDF417
<b>Tear Bar</b>	Embedded in printer mechanism
<b>Mount</b>	Rubber pads for desk mount Two threaded inserts for hard mount. Optional mounting solutions available.
<b>Regulatory Approvals</b>	FCC, CE
<b>Drop Specification</b>	1 m (3.3') with soft skin case
<b>Battery/Power</b>	7.4V 1400mAH replaceable Lithium-ion battery, self discharge rate <10% week, AC charging adapter 100-240VAC, 50/60 Hz
<b>Dimensions(W x D x H)</b>	75 x 96 x 46 mm (3.0 x 3.8 x 1.8" )
<b>Weight</b>	270g/9.5oz/0.60 lbs (paper and battery included)
<b>Software/ Development</b>	Developer guide includes reference code for Apple iOS, Java, Windows Mobile, and WinCE OS environments.
<b>Environment</b>	Operating temperature: -5 ~ 50°C (+23 ~ 122°F) Operating humidity: 20 ~ 85% RH Storage temperature: -20 ~ 60°C (-4 ~ 140°F) Storage humidity: 5 ~ 90% RH
<b>Expected Life</b>	Print Head: 50 km (31 miles), 400 million dot lines @ 12.5% print ratio Battery: single charge: 20 m (66 ft), 12.5% print ratio, 500 charge cycles Clamshell: 5,000 times open/close
<b>Included Accessories</b>	Power Adapter (100~240 VAC, 50/60 Hz) Cable (USB or Serial) Paper Roll (15 m in length) Sturdy Rubber Skin Case Hip Mount Belt Buckle
<b>Optional Accessories</b>	Spare Battery Car Charger Carrying Case



All features and specifications are subject to change without notice. All trademarks mentioned are registered by their respective owners. Contact Blue Bamboo sales for more details.

Also see Blue Bamboo **PocketPOS™ P25i-M** which includes magnetic-stripe reader

**Blue Bamboo Corporate Offices**  
6 Floor, Huishan Technology Park,  
3333 Changning Road, Shanghai China 200336  
Tel: +86 21 5219 0333 Fax: +86 21 5219 0603  
USA Office Tel: 1-888-372-9266



**BLUE BAMBOO®**